

WEB P1 Percentage Loading Chart

PORT

Percentage	Capacity	Gauge Height
50%	3759.70	8' - 4"
60%	4511.64	9' - 7 3/4"
70%	5263.58	11' - 0"
75%	5639.55	11' - 8 3/4"
80%	6015.52	12' - 5"
85%	6391.49	13' - 2 1/4"
86%	6466.68	13' - 4 1/4"
87%	6541.88	13' - 6 1/4"
88%	6617.07	13' - 8 1/4"
89%	6692.27	13' - 10 1/4"
90%	6767.46	14' - 0 1/2"
91%	6842.65	14' - 2 3/4"
92%	6917.85	14' - 5"
93%	6993.04	14' - 7 1/4"
94%	7068.24	14' - 9 3/4"
95%	7143.43	15' - 0 1/2"
96%	7218.62	15' - 3 1/4"
97%	7293.82	15' - 6"
98%	7369.01	15' - 9 1/2"
99%	7444.21	16' - 1 1/2"
100%	7519.40	16' - 8 1/8"

Total Capacity 7519.4

STBD

Percentage	Capacity	Gauge Height
50%	3769.02	8' - 4"
60%	4522.82	9' - 7 3/4"
70%	5276.63	11' - 0"
75%	5653.53	11' - 8 1/4"
80%	6030.43	12' - 5"
85%	6407.33	13' - 2 1/4"
86%	6482.71	13' - 4 1/4"
87%	6558.09	13' - 6 1/4"
88%	6633.48	13' - 8 1/4"
89%	6708.86	13' - 10 1/4"
90%	6784.24	14' - 0 1/2"
91%	6859.62	14' - 2 3/4"
92%	6935.00	14' - 5"
93%	7010.38	14' - 7 1/4"
94%	7085.76	14' - 9 3/4"
95%	7161.14	15' - 0 1/2"
96%	7236.52	15' - 3 1/4"
97%	7311.90	15' - 6"
98%	7387.28	15' - 9 1/2"
99%	7462.66	16' - 1 1/2"
100%	7538.04	16' - 8 1/8"

Total Capacity 7538.04